Main features

- Up to twelve 5.5kW PSUs
- High efficiency up to 97.5% (peak)
- 50V/48V output
- Single/dual AC feed possible
- PSC with Redfish communication
- · Possibility to customized on request
- Industry standard footprint

Applications

- Al servers
- Hyperscale Cloud Services

Dimensions (H x W x L)

44 x 465 x 766 mm / 1.73 x 18.3x 30.1 in

Part number	Flex GB200
Output power max.	33kW
Output voltage	50V
Output current	760A
Input voltage range	AC input: 200-277VL-N 346-480V L-L (3 W+N+PE) 50/60Hz
Cooling	Cooling by PSU fans
Input connectors	SP10RSSS48M220A1/AA-2269 SP10RSSS48RM220A1/AA-226
Output connectors	BK600
Safety	IEC60950-1(CB) UL60950-1(CAN/CSA)
EMC Standards	Class A
Communication	MODBUS over RS-485



1RU power shelf



Bus bar clip



PSC Module



5500W PSU

Flex (Reg. No. 199002645H) is the manufacturing partner of choice that helps a diverse customer base design and build products that improve the world. Through the collective strength of a global workforce across 30 countries and responsible, sustainable operations, Flex delivers technology innovation, supply chain, and manufacturing solutions to various industries and end markets.

For more information, visit flex.com.

